



A68HM GRENADE (MS-7891v1.1) m-ATX Motherboard

Supports FM2+ Socket for AMD®
A- series/ Athlon™ Series Processor



Motherboard Specification

| | |
|---|---|
| <p>Processor Support</p> <ul style="list-style-type: none"> Supports FM2+ Socket for AMD® A- series/ Athlon™ Series Processor <p>Chipset</p> <ul style="list-style-type: none"> AMD® A68H chipset <p>Memory Support</p> <ul style="list-style-type: none"> 2 DIMMs support for DDR3-2133(O.C)/1866/1600/1333 MHz up to 32GB max Supports dual channel mode <p>LAN</p> <ul style="list-style-type: none"> Supports Gb LAN 10/100/1000 Fast Ethernet by Realtek® RTL8111G <p>Audio</p> <ul style="list-style-type: none"> Chip integrated by Realtek® ALC887 Flexible 8-channel audio with jack sensing Compliant with Azalia 1.0 Spec <p>SATA</p> <ul style="list-style-type: none"> 4 SATA 6Gb/s ports by AMD® A68H <p>USB3.0</p> <ul style="list-style-type: none"> 2 USB 3.0 ports by AMD® A68H (rear x 2) 2 USB 3.0 ports by VIA VL806 (front x 2) | <p>Connectors</p> <ul style="list-style-type: none"> Back panel <ul style="list-style-type: none"> 1 PS/2 mouse port 1 PS/2 keyboard port 1 VGA port 1 DVI port 1 HDMI port 4 USB 2.0 ports 2 USB 3.0 ports 1 LAN jack 3 flexible audio jacks On-Board Connectors <ul style="list-style-type: none"> 2 USB 2.0 connectors 1 USB 3.0 connector 1 Front Panel Audio connector 1 Serial connector 1 TPM Module connector 1 Chassis Intrusion connector <p>Slots</p> <ul style="list-style-type: none"> 1 PCI Express x16 slot 1 PCI Express x1 slot 1 PCI slot, Support 3.3V/ 5V PCI bus Interface <p>Form Factor</p> <ul style="list-style-type: none"> Micro-ATX (22.6 cm X 18.6 cm) <p>Feature on Focus</p> <ul style="list-style-type: none"> M-Flash included USB Safeguard Directx 11 Dual Graphic AMD Memory profile technology <p>Mounting</p> <ul style="list-style-type: none"> 6 mounting holes |
|---|---|

These specification is subject to change without prior notice.