



# H81M-E34 (MS-7817v3.0) m-ATX Motherboard

Support 4th Generation Intel® Core Processors for LGA 1150 socket





# **Motherboard Specification**

# **Processor Support**

Support 4<sup>th</sup> Generation Intel<sup>®</sup> Core Processors for LGA 1150 socket

#### Base Clock

■ 100 MHz

#### Chipset

■ Intel® H81 chipset

## Memory Support

- 2 DDR3 DIMMs support 1066/ 1333/ 1600 DRAM (16GB Max)
- Supports Dual-Channel mode

#### LAN

■ Supports Gb LAN 10/100/1000 by Realtek® RTL8111G

#### Audio

- Chip integrated by Realtek® ALC887
- Flexible 8-channel audio with jack sensing
- Compliant with Azalia 1.0 Spec

#### SATA

- 2 SATA 6Gb/s (SATA3~4) ports by Intel® H81
- 2 SATA 3Gb/s (SATA1~2) ports by Intel® H81

#### USB 3.0

- 2 USB 3.0 ports by Intel® H81 (front x 2)
- 4 USB 3.0 ports by VIA® VL805 (rear x 4)

# Connectors

- Back panel
  - 1 PS/2 keyboard port
  - 1 PS/2 mouse port
  - 2 USB 2.0 ports
  - 4 USB 3.0 ports
  - 1 VGA port
  - 1 DVI port
  - 1 HDMI port
  - 1 LAN port
  - 3 flexible audio ports

#### ■ On-Board

- 2 USB 2.0 connectors
- 1 USB 3.0 connector
- 1 Chassis Intrusion connector
- 1 Front Panel Audio connector
- 1 Serial port connector1 TPM Module connector

#### Slots

- 1 PCIE x16 slot
- 2 PCIE x1 slots

# Form Factor

■ Micro-ATX (22.6 cm X 17.3 cm)

## Feature on Focus

- Command Center
- M-Flash
- Military Class 4
- OC Genie 4
- SATA 6G
- USB3.0

# Mounting

■ 6 mounting holes

These specification is subject to change without prior notice.